



# DECOWOOD

## WOOD EFFECT DECORATIVE PROTECTION PANEL

### Applications

This panel has been designed to protect from impact and abrasion whilst offering the warmth and style of a wood effect finish. The product can be thermoformed for use on round pillars (diameter under 800 mm) and to ensure a perfect hygiene in the angles. It is particularly adapted to retirement homes, clinics, schools, hotels...

### Description

- Model: Decowood decorative protection panel
- Standard panel dimensions: 3 m x 1.30 m
- Thickness: 2 mm
- Material: wood effect Bs2d0 fire-rated PVC
- Surface finish: wood effect
- Fixing: adhesive bonding with SPM acrylic glue or SPM universal mastic glue. Joints between panels can be made using silicone joints or PVC welding rods, colour matched to the range.
- Colours: 7 standard wood effect finishes

### Specification

- Description : 2 mm thick wood effect decorative protection panel (Decowood as manufactured by SPM) from rigid wood effect PVC achieving Bs2d0 fire rating and impact and scratch resistance. A protective film is specified to minimise cleaning before acceptance. 3.00 long, 1.30 high.
- Environment: no heavy metals and no substance potentially subjected to any REACH restriction are used in its manufacture, nor PBT/BPA. The calcium-zinc thermal stabilisation process is used. The emission level of volatile substance in inside air has been tested according to ISO 16000-6 and is very low (A+) according to the French regulation (23 March 2011 nr 2011-321 Decree and 19 April 2011 Order). 100% of the product are recyclable.
- Colour: selected by architects from manufacturer's standard range.
- Installation method: glue as per manufacturer's instructions.

